

1: GLAZING MATERIAL

- ACRYLIC DOME INNER OUTER
- POLYCARBONATE DOME
- TWIN WALL POLYCARBONATE 6MM 8MM 10MM 16MM
- TRIPLE WALL POLYCARBONATE 16MM

2: GLAZING COLOR

- CLEAR
- BRONZE N/A
- WHITE
- OTHER _____
- TWIN WALL CLEAR
- OR BRONZE
- TRIPLE WALL WHITE

3: FRAME FINISH


- MILL
- BRONZE ANODIZED
- CLEAR ANODIZED
- CUSTOM COLOR _____

4: PYRAMID PITCH (OPTIONAL)

- 22 DEGREE (1/2 WIDTH X .414)
- 30 DEGREE (1/2 WIDTH X .577)
- 40 DEGREE (1/2 WIDTH X .839)

FOR CURB MOUNT SKYLIGHTS PROVIDE
OUTSIDE DIMENSION OF FINISHED CURB

- QTY: O.D. CURB= X
- QTY: O.D. CURB= X
- QTY: O.D. CURB= X
- QTY: O.D. CURB= X
- QTY: O.D. CURB= X



CURB MOUNT



AMERICAN SKYLITES
525 113th STREET ARLINGTON, TEXAS 76011
Phone 800.772.7401 Fax 800.445.7282

TEST METHOD	TEST PRESSURE	ALLOWED
AIR INFILTRATION ASTM E283	6.24 PSF (50 MPH)	0.03 CFM/FT
WATER PENETRATION ASTM E547/E331	TEST PRESSURE 15.0 PSF	NO LEAKAGE
UNIFORM LOAD ASTM E330	POSITIVE 69.0 PSF NEGATIVE 75.0 PSF	60.0 PSF MIN 40.0 PSF MIN